NuTone®

Under-Cabinet

MANTRA

The slim curves of Mantra are the perfect complement to today's modern kitchens. Advanced features, like LED lighting and 2 fan speeds make operation enjoyable. The LED modules included with this hood are the latest in LED cooktop illumination technology specially designed to operate in the elevated temperatures of cooking - offering bright lighting and lasting up to 25 times as long as a standard bulb and greater reliability than typical replacement LED bubs.

SIZE	WHITE	BLACK	BLACK STAINLESS	STAINLESS	GREASE FILTERS (replacement)	NON-DUCTED FILTERS
30 in.	AVSF130WW	AVSF130BL	AVSF130BLS	AVSF130SS	HPFA130 (Type C1)	HPF30 (Type Xc)
36 in.	AVSF136WW	AVSF136BL	AVSF136BLS	AVSF136SS	HPFA136 (Type D1)	HPF36 (Type Xd)

HVI PERFORMANCE

Duct Orientation	Size	Damper	Sones		CFM		
			Normal	High	Normal	High 0.25 in. w.g.	High 0.1 in. w.g.
Vertical - Rectangular	3¼ in. x 10 in.	Included	1.5	5.5	130	160	250
Horizontal - Rectangular	3¼ in. x 10 in.	Included	1.5	6.0	110	160	240
Round - Vertical	7 in.	Sold Separately	1.5	5.5	140	150	280

FEATURES	
Max. Blower CFM*	375
Control type	2-speed Rocker
Delay off	no
Filter Clean Reminder	no
Heat Sentry™	no
ADA Capable	yes
Lighting	1-level LED (included)
Grease Filters	Open Mesh (Qty. 2)
Installation Hardware	EZ1 brackets
ENERGY STAR®	no
Recirculation	Non-ducted filters sold separately

AC INPUT

120 V, 60 Hz - 0.65 AMPS

OPTIONAL ACCESSORIES

7-in. Round Damper	BP87Q
Make-up Air Dampers	MD6TU, MD8TU and MD10TU

MOUNTING HEIGHT

18 in. to 24 in. from cooktop to bottom of hood

LIMITED WARRANTY

1-year
3-year (LED modules only)
See installation manual for full warranty text.

FOR INDOOR USE ONLY





Dimensions shown in inches.

HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in AMCA's state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.

* Max. blower CFM indicates the performance of the hood blower in open air.

SPECIFICATION SHEET

MANTRA - AVSF1 SERIES